



17 19 /

DN 80, 125, 150 PN16



- +225°
- ( / ²):

PN.....1,6 (16)  
.....0,2.....1,6 (2.....16)

- 59-1, 18,

- 17 19 /

**ТЕХНИЧЕСКИЕ ПАРАМЕТРЫ**

DN	/	( / ²)			Ln,	
80 (50 2)	17 19	0,3-0,6 (3-6)	2	11,5	210-540	59,0
	17 19 1	0,7-1,1 (7-11)	4		363-537	82,0
	17 19 2	1,2-1,6 (12-16)	6		390-535	105,0
125 (80 2)	17 19	0,2-0,5 (2-5)	2	24,0	220-790	109,0
	17 19 1	0,6-0,9 (6-9)	4		510-755	157,0
	17 19 2	1,0-1,3 (10-13)	6		565-715	205,0
	17 19 3	1,4-1,6 (14-16)	8		595-680	253,0
150 (100 2)	17 19	0,2-0,4 (2-4)	2	27,0	285-713	136,0
	17 19 1	0,5-0,7 (5-7)	4		473-700	190,0
	17 19 2	0,8-1,0 (8-10)	6		536-700	244,0
	17 19 3	1,1-1,3 (11-13)	8		583-698	298,0
	17 19 4	1,4-1,6 (14-16)	10		605-697	352,0